



## DESCRIPTION

Integral Series 92 is a Miniature Rotary Switch of 25 mm Dia offering premium quality at economical price. The design of the Switch is limited to a single section with solder/pc terminals. These are totally enclosed switches offering the most popular combination as encountered in modern electronic circuits. Uniform, positive indexing is provided by 2 balls housed in a Engineering Plastic case.

## SPECIFICATIONS

CONTACT RATING:	2.5 A @ 125 V Ac or 28 V Dc 150 mA @ 250V Ac or Dc
CONTINUOUS CURRENT:	5A
LIFE:	More than 15,000 cycles on full load
CONTACT RESISTANCE:	Less than 15 milli ohms measured at 2-4 V DC/100 mA
WORKING VOLTAGE:	230 V AC(max)
INSULATION:	Better than 1000M Ohms.
VOLTAGE PROOF:	1000 V RMS
OPERATING TEMPERATURE:	- 30 <sup>0</sup> C to + 85 <sup>0</sup> C
INDEXING ANGLE:	30 <sup>0</sup> .
MATERIALS	
BODY, ROTOR & BASE:	Glass filled Nylon
CONTACT:	Copper alloy or coin silver . Silver plate or gold plate.
HARDWARE:	Brass/ Steel Zinc plate.